

MacDermid Enthone

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET

LACOMIT REMOVER

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : LACOMIT REMOVER
Product code : 160059

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Solvent
Industrial applications.

1.3 Details of the supplier of the safety data sheet

e-mail address of person responsible for this SDS : sdsuk@macdermid.com; regulatory.de@macdermid.com

Supplier : MacDermid Performance Solutions UK Limited
198 Golden Hillock Road
Birmingham
B11 2PN
UK
HSO Herbert Schmidt GmbH & Co. KG
Schorberger Str. 18 - 26
42699 Solingen
Germany

Information contact : Tel (+44) 121 606 8100
ukcustomer.services@macdermid.com
HSO Tel: (+49) 212 65850

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : UK NPIS 0344 892 0111 (Healthcare professionals only)

Supplier

Telephone number : Carechem24: (+44) 1865 407333; (+44) 1235 239 670 (across Europe)
Hours of operation : 24/7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Flam. Liq. 2, H225

Skin Irrit. 2, H315

Eye Irrit. 2, H319

STOT SE 3, H335

STOT SE 3, H336

STOT RE 2, H373

Asp. Tox. 1, H304

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements :

- H225 - Highly flammable liquid and vapour.
- H304 - May be fatal if swallowed and enters airways.
- H315 - Causes skin irritation.
- H319 - Causes serious eye irritation.
- H335 - May cause respiratory irritation.
- H336 - May cause drowsiness or dizziness.
- H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention :

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P260 - Do not breathe vapour.

Response :

- P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

Storage :

- P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

Disposal :

- P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazardous ingredients :

- acetone
- xylene

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Special packaging requirements

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII : This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification : None known.

SECTION 3: Composition/information on ingredients**3.2 Mixtures** : Mixture

Product/ingredient name	Identifiers	%	Classification	Type
acetone	REACH #: 01-2119471330-49 EC: 200-662-2 CAS: 67-64-1 Index: 606-001-00-8	≥75 - ≤90	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	[1] [2]
xylene	EC: 215-535-7 CAS: 1330-20-7 Index: 601-022-00-9	≥10 - <25	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 See Section 16 for the full text of the H statements declared above.	[1] [2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If material has been ingested or inhaled, do not give mouth-to-mouth respiration.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

SECTION 4: First aid measures

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact : Adverse symptoms may include the following:
irritation
redness

Ingestion : Adverse symptoms may include the following:
nausea or vomiting

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water. Liquid will float and may reignite on surface of water.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture : Highly flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapour or mist. Do not swallow. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

SECTION 7: Handling and storage

Store between the following temperatures: 5 to 40°C (41 to 104°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : No specific measures identified.

Industrial sector specific solutions : No specific measures identified.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
acetone	EH40/2005 WELs (United Kingdom (UK), 1/2020). STEL: 3620 mg/m ³ 15 minutes. STEL: 1500 ppm 15 minutes. TWA: 500 ppm 8 hours. TWA: 1210 mg/m ³ 8 hours.
xylene	EH40/2005 WELs (United Kingdom (UK), 1/2020). [xylene, o-,m-,p- or mixed isomers] Absorbed through skin. STEL: 441 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 220 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes.

Recommended monitoring procedures : Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

EU DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
acetone	DNEL	Long term Oral	62 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	62 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	186 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	200 mg/m ³	General population	Systemic
	DNEL	Long term Inhalation	1210 mg/m ³	Workers	Systemic
	DNEL	Short term Inhalation	2420 mg/m ³	Workers	Local
xylene	DNEL	Long term Oral	12.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Local
	DNEL	Long term Inhalation	65.3 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	125 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	212 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	221 mg/m ³	Workers	Systemic

SECTION 8: Exposure controls/personal protection

	DNEL	Short term Inhalation	260 mg/m ³	General population	Local
	DNEL	Short term Inhalation	260 mg/m ³	General population	Systemic
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Local
	DNEL	Short term Inhalation	442 mg/m ³	Workers	Systemic

EU PNECs

No PNECs available

8.2 Exposure controls

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If inhalation hazards exist, a full-face respirator may be required instead. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Chemical splash goggles. Use eye protection according to EN 166. Contact lenses should not be worn when working with this chemical!

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Recommendations: In splash contact: 1 - 4 hours (breakthrough time): butyl rubber (thickness: 0.5 mm) Wear suitable gloves tested to EN374.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties**Appearance**

Physical state	: Liquid.
Colour	: Colourless. [Transparent]
Odour	: Ketone.
Odour threshold	: There are no data available on the mixture itself.
Melting point/freezing point	: There are no data available on the mixture itself.
Initial boiling point and boiling range	: 50°C (122°F)
Flammability (solid, gas)	: There are no data available on the mixture itself.
Upper/lower flammability or explosive limits	: There are no data available on the mixture itself.
Flash point	: Closed cup: 18°C (64.4°F)
Auto-ignition temperature	: 363°C (685.4°F)
Decomposition temperature	: There are no data available on the mixture itself.
pH	: Not applicable.
Viscosity	: Kinematic (40°C): <20 mm ² /s
Solubility(ies)	:

Media	Result
cold water	Partially soluble

Solubility in water	: There are no data available on the mixture itself.
Miscible with water	: Yes.
Partition coefficient: n-octanol/ water	: Not applicable.

Vapour pressure :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
acetone	180.01	24				

Evaporation rate	: There are no data available on the mixture itself.
Relative density	: There are no data available on the mixture itself.
Density	: 0.9 to 0.95 g/cm ³ [20°C (68°F)]
Vapour density	: >1 [Air = 1]
Explosive properties	: There are no data available on the mixture itself.
Oxidising properties	: There are no data available on the mixture itself.
Particle characteristics	
Median particle size	: Not applicable.

9.2 Other information

SAPT	: Not relevant/applicable due to nature of the product.
-------------	---

SECTION 10: Stability and reactivity

- 10.1 Reactivity** : Extremely reactive or incompatible with the following materials: oxidising materials, acids and alkalis.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials: oxidising materials
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
acetone	LD50 Oral	Rat	5800 mg/kg	-
xylene	LC50 Inhalation Gas. LD50 Oral	Rat Rat	5000 ppm 4300 mg/kg	4 hours -

Conclusion/Summary : Not tested

Acute toxicity estimates

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
LACOMIT REMOVER	N/A	5500.0	N/A	N/A	7.5
acetone	5800	N/A	N/A	N/A	N/A
xylene	4300	1100	N/A	N/A	1.5

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	395 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
xylene	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 uL	-
	Skin - Moderate irritant	Rabbit	-	100 %	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-

Conclusion/Summary

- Skin** : Not tested
- Eyes** : Not tested

SECTION 11: Toxicological information**Respiratory** : Not tested**Sensitisation****Conclusion/Summary****Skin** : Not tested**Respiratory** : Not tested**Mutagenicity****Conclusion/Summary** : Not tested**Carcinogenicity****Conclusion/Summary** : Not tested**Reproductive toxicity****Conclusion/Summary** : Not tested**Teratogenicity****Conclusion/Summary** : Not tested**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
acetone	Category 3	-	Narcotic effects
xylene	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
xylene	Category 2	-	-

Aspiration hazard

Product/ingredient name	Result
xylene	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not tested**Potential acute health effects****Eye contact** : Causes serious eye irritation.**Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.**Skin contact** : Causes skin irritation.**Ingestion** : Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways.**Symptoms related to the physical, chemical and toxicological characteristics****Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness**Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

SECTION 11: Toxicological information

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- Conclusion/Summary** : Not available.
- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Reproductive toxicity** : No known significant effects or critical hazards.

Other information : No known significant effects or critical hazards.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
acetone	Acute EC50 20.565 mg/l Marine water	Algae - Green algae - <i>Ulva pertusa</i>	96 hours
	Acute LC50 4.42589 ml/L Marine water	Crustaceans - Calanoid copepod - <i>Acartia tonsa</i> - Copepodid	48 hours
	Acute LC50 10000 µg/l Fresh water	Daphnia - Water flea - <i>Daphnia magna</i>	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Guppy - <i>Poecilia reticulata</i>	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Green algae - <i>Ulva pertusa</i>	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphnia - <i>Daphniidae</i>	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Water flea - <i>Daphnia magna</i> - Neonate	21 days
xylene	Chronic NOEC 5 µg/l Marine water	Fish - Threespine stickleback - <i>Gasterosteus aculeatus</i> - Larvae	42 days
	Acute LC50 8500 µg/l Marine water	Crustaceans - Daggerblade grass shrimp - <i>Palaemonetes pugio</i>	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Fathead minnow - <i>Pimephales promelas</i>	96 hours

Conclusion/Summary : Ecological testing has not been conducted on this product.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
LACOMIT REMOVER	-	-	Readily
acetone	-	-	Readily
xylene	-	-	Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
acetone	-0.23	-	Low
xylene	3.12	8.1 to 25.9	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : The classification of the product may meet the criteria for a hazardous waste.





Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S. (acetone, xylene)	FLAMMABLE LIQUID, N.O.S. (acetone, xylene)	FLAMMABLE LIQUID, N.O.S. (acetone, xylene)
14.3 Transport hazard class(es)	3 	3  	3 
14.4 Packing group	II	II	II
14.5 Environmental hazards	No.	Yes.	Yes. The environmentally hazardous substance mark is not required.

Additional information

- ADR/RID** : **Special provisions** 640 (C)
Tunnel code D/E
- IMDG** : The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.
Emergency schedules F-E, S-E
- IATA** : The environmentally hazardous substance mark may appear if required by other transportation regulations.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments : Not applicable - not transported in bulk

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture UK (GB)/REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

Seveso Directive - Reporting thresholds

Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c	5000 tonne	50000 tonne

SECTION 15: Regulatory information

EU regulations

Industrial emissions (integrated pollution prevention and control) - Air : Listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

✔ Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
STOT SE 3, H335	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method
Asp. Tox. 1, H304	Calculation method

Full text of abbreviated H statements

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

SECTION 16: Other information

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Flam. Liq. 2	FLAMMABLE LIQUIDS - Category 2
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

Date of printing : 11 November 2024

Date of issue/ Date of revision : 8 November 2024

Date of previous issue : 2 May 2023

Version : 1.02

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

MacDermid Enthone SDS CLP Europe
(transfer)